



DESIGN CONCEPT



Following the prior introduction of the Strike-X ST case, the Strike-X GT (stands for Gaming Tower) is finally here to meet the needs of those who are in need of a high-end case but a lesser appetite for space.

The Strike-X GT offers great flexibility for expansion with excellent cooling ability. With the HDD convertors included in this case, user can easily install up to 7x 2.5" HDDs or 3.5" HDDs, and furthermore, each convertor also acts as a fan bracket for a 12cm fan to be mounted at the opposite site of the HDD to cool the heat that HDD generates. Moreover, the convertors can also be mounted vertically to the front of chassis with a 12cm fan installed to draw in cool air to force out the heat to the rear of chassis.

If you are concerned with the heat issue in a PC case and yet want to keep the expansion ability, Strike-X GT is the case of your choice.

GT BLACK / DEVIL RED

FERTURES



- High performance "Mid-Tower" for gamers and enthusiast.
- Aggressive "X" concept design case a gamers' dream!
- Supports longer high-end VGA cards up to 295 mm.
- Supports 3 x 5.25" bays and maximum 6 x 2.5"/3.5" HDDs (internal) with HDD convertor bracket.
- Anti-vibration pad included to dampen PSU vibration.
- Each HDD bracket can mount a 12cm fan to cool each individually.
- "Easy-install" screw-less kits for the 5.25" devices.
- 3 x USB2.0 + 1 x USB3.0 and Audio/Mic ports are easily accessible from the top of case.
- CPU hole is pre-drilled on the Motherboard for easy access to cooler installation.
- Cable management holes are pre-drilled with high end rubber protection.
- Dust filter included to prevent dust entering from the bottom of case.
- Supports water-cooling



GALLERY













GALLERY















57 BLACK / DEVIL RED

CRSE

SPECIFICATIONS

Case type : Mid Tower

Material SECC 0.6mm

Motherboard : Micro ATX/ATX

Case dimensions : 465mm (H) x 190mm (W) x 490mm (D)

Drive bays : 3x 5.25" (Exposed) / 9 x 3.5" HDD or 2.5" HDD

Expansion slots :

Max. length space available for PCI slots : 295mm

I/O ports 1x USB 3.0 / 3x USB2.0 / Audio+Mic

COOLING SYSTEM

Front 120 x 120 x 25 mm "Quad RED LEDs"



Back 120 x 120 x 25 mm "Quad RED LEDs"



Rated Voltage : 12V 12V

Starting Voltage : <=6V(Power ON/OFF) <=6V(Power ON/OFF)

Power Consumption : 1.2W 1.2W

Rated Current : 0.2A 0.2A

Speed : 1200 1200

Air Flow : 39 CMF -H2O 39 CMF -H2O

Noise : 23dBA 23dBA

MTBF : 20000 hours 20000 hours



AIR FLOW

Superb airflow - install up to 8 fans !!

- 1. Front 2 x 12cm RED LED fans (1 x 12cm included)
- 2. Top 2 x 12 cm fans (optional)
- 3. Bottom 1 x 14cm fan (optional) (Fan screws must penetrate the dust filter)
- 4. Left Side 2 x 12cm fans (optional)
- 5. Rear 1 x 12cm RED LED fan (included)



STRIKE GT BLACK / DEVIL RED

INSIDE








Dust Filter for PSU



Can install up to 2x 12 cm fans on top panel



Pre-drilled hole for easy access to CPU mounting bracket



Tool-free for 5.25" bay



USB 3.0 x 1 & USB 2.0 x 3



Can install 1 x 14cm fan at bottom of case (Fan screws must penetrate the dust filter)



Can install up to 2x 12 cm fans on front panel




Install up to 2 x 12cm fans on side panel



Perforated PCI slot for better air flow



Pre-drilled holes for cable management



PSU Anti-vibration pad



Pre-drill pipe holes for water cooling



Sufficient depth of chassis for installing long cards

CLOSE UP



CLOSE UP



57RIKE X